



ECTBC-90

Cover Bend 90° Cable Tray ECTB-90



- ✓ Standard execution **hot dip galvanized carbon steel** in accordance with NEN-EN-ISO 1461
- ✓ High zinc coating thickness of **at least 60 µm**
- ✓ Also available in **pre-galvanized, stainless steel 316L** and **stainless steel 304**
- ✓ Standard width 75–600 mm
- ✓ Standard radius for accessories 50°
- ✓ Standard angles for accessories 45° and 90°
- ✓ Other widths, angles and radii available on request

Description


The ECTBC90 cover is an accessory for the ECT60 and ECT100 cable tray systems and is used to cover horizontal 90° bends, specifically designed for the ECTB60-90 and ECTB100-90 bends. The cover ensures a closed and protected cable route at the point of direction change and prevents the ingress of dust and dirt. This accessory is suitable for heavy industrial, utility, and infrastructure installations.

The standard execution is manufactured from hot-dip galvanized carbon steel in accordance with NEN-EN-ISO 1461, with a zinc coating thickness of at least 60 µm, making it suitable for heavy industrial and outdoor environments. The hot-dip galvanizing process is applied after fabrication and provides durable corrosion protection of the surface, including cut edges, in accordance with IEC 61537 and installations according to NEN 1010.

The cover is specifically designed for installation on the horizontal 90° bends ECTB60-90 and ECTB100-90. Fixing is carried out using the ECTCC60 cover clamp (not included), ensuring stable and vibration-resistant fixation. The execution is fully compatible with the corresponding bends and other system components within the ECT system.

Technical specifications

Product type:	Cover for bend 90° ECTB-90
Compatibility:	ECTB60-90 and ECTB100-90
System:	ECT60 and ECT100
System height:	60 mm and 100 mm
System width:	75 to 600 mm
Material thickness:	1.0 to 1.5 mm
Height:	10 mm
Angle:	90°
Radius:	50 mm
Change of direction:	Horizontal
Standard material:	Carbon steel
Surface treatment:	Hot-dip galvanized in accordance with NEN-EN-ISO 1461
Zinc coating thickness:	Minimum 60 µm
Installation:	Secured with ECTCC60 cover clamp (not included)
Standards:	IEC 61537, applicable within installations in accordance with NEN 1010



Available material variants


PG: Pre-galvanized steel (EN 10346), suitable for dry indoor environments and light industrial applications.

HDG: Hot-dip galvanized carbon steel in accordance with NEN-EN-ISO 1461, with a high coating thickness of at least 60 µm, suitable for heavy industrial and outdoor environments.

SS 304 (A2 / 1.4301): Stainless steel for indoor environments and lightly corrosive conditions.

SS 316L (A4 / 1.4404): Stainless steel with increased corrosion resistance for chemical, maritime, and offshore applications.

Other widths, radii and angles available on request.



Variants

Article number	W mm	H mm	A deg°	R mm	e mm
ECTBC-075-90-HDG	78	10	90	50	1.0
ECTBC-100-90-HDG	103	10	90	50	1.0
ECTBC-150-90-HDG	153	10	90	50	1.0
ECTBC-200-90-HDG	203	10	90	50	1.0
ECTBC-300-90-HDG	303	10	90	50	1.0
ECTBC-400-90-HDG	403	10	90	50	1.5
ECTBC-500-90-HDG	503	10	90	50	1.5
ECTBC-600-90-HDG	603	10	90	50	1.5

Available material variants	Change HDG to
Hot dip galvanized	-
Pre-galvanized (PG)	PG
Stainless steel A4 / 316L	SS316
Stainless steel A2 / 304	SS304

Different material thickness

PG	SS316	SS304	e mm
ECTBC-400-90-PG	ECTBC-400-90-SS316	ECTBC-400-90-SS304	1.0

